leolux LX

LX662 Design: Frans Schrofer, 2015



Technical details

<u>Model</u>

Inner frame Inner frame seat	Metal frame foamed Metal frame
Inner frame footstool Springs seat footstool	Sheet material Elastic belts
Wadding	PU/HR foam 50/30kg/m³, wadding Leoskin HR foam 50kg/m³, wadding Leoskin HR foam 40kg/m³, wadding Leoskin HR foam 20kg/m³, wadding Leoskin Polyether foam 30kg/m³, wadding Leoskin
<u>Upholstery</u>	
Upholstery Stitching Decorative stitch	Fabric or leather Colour-to-colour or one of the standard colours. Flat seam, double stitch and Artisan
Exception	Upholstery in patterned strains is not possible towards design and seam layout
<u>Legs</u>	
Swivel base armchair - 5-legged swivel base - 4-legged swivel base	Aluminium polished or all standard epoxy colours (powder coating) Aluminium polished or all standard epoxy colours (powder coating)
Auto-return mechanism	Optional: Auto-return mechanism (excluded in combination with 5-arms swivel base height +2cm)
Lever and Column Gliders	Chrome plated (at aluminium base) Matching lacquer (with epoxy / lacquered foot) Synthetic, black

Technical details

<u>Functions</u>	
Tilting mechanism	Version LX662-100
Seat heights	+2cm
<u>Comments</u>	
Deviating stitching	When opting for different stitching colours, this option applies to the entire piece of furniture. If the inside and outside are selected with two different deviating stitching colours, this must be explicitly stated on the order. De- viating stitching is not possible on the decorative stitch Artisan, it always is the colour of the stitching for the outside.
Certifications	All sheet materials used in this model comply with the CARB2 requirement or are NAF certified
	On request foam materials with additional flame retardants can be applied.

Technical drawings

